



CUT LENGTHWISE



CUT CROSSWISE

VIEW

SAGLAN (032) SR 30

SAGLAN Sparrenplatten

Sager AG

<http://www.sager.ch/> | info@sager.ch

Type: **Insulation | Cemented**

Ohne Strichmarkierung

Für SAGLAN Glaswolle wird natürlicher Quarzsand geschmolzen, zu feinen Glasfasern versponnen und zu unbrennbaren Glaswolleplatten oder Rollfilzen weiterverarbeitet. Diverse Beschichtungen, wie z.B. Glasvlies oder Aluminium erweitern den Einsatzbereich unsere Glaswolle Produkte. Mit SAGLAN Glaswolle erreicht man einen ausgezeichneten Schallschutz und Wärmedämmwert.

mtextur ID	20985
Manufacturer	Sager AG
Manufacturer-Email	info@sager.ch
Product Line	SAGLAN Sparrenplatten
Product Line Info	Für SAGLAN Glaswolle wird natürlicher Quarzsand geschmolzen, zu feinen Glasfasern versponnen und zu unbrennbaren Glaswolleplatten oder Rollfilzen weiterverarbeitet. Diverse Beschichtungen, wie z.B. Glasvlies oder Aluminium erweitern den Einsatzbereich unsere Glaswolle Produkte. Mit SAGLAN Glaswolle erreicht man einen ausgezeichneten Schallschutz und Wärmedämmwert.
Material Name	SAGLAN (032) SR 30
Type	Insulation / Cemented
Material Info	Ohne Strichmarkierung
eBKP	C 1.2 Abdichtung, Dämmung und Bodenplatte / C 1.2 Waterproofing/insulation below ground slab
IFC	IfcCovering
Area of application (mtextur Classic)	Inside / Floor / Wall / Ceiling / Roof / Facade Outside / Floor / Wall / Ceiling / Roof / Facade
Delivery zones	CH / LI
Size of the CAD & BIM texture	Height: 400.0 mm / Width: 400.0 mm

IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.

max. Length / Format	Length = 1250 mm / Width = 1000 mm / Thickness = 260 mm
min. Format	Length = 1250 mm / Width = 400 mm / Thickness = 60 mm
Weight	30.0 kg/m ³
Thermal Conductivity	0.032 W/mK
Fire protection class	6q.3 A1
Characteristics Info	<p>Halbsteife Platten, durchgehend imprägniert, selbstklemmend zwischen Sparren, halten ohne zusätzliche Befestigung.</p> <p>Das Haupteinsatzgebiet ist zwischen den Sparren mit regelmässigen Abständen, bei Holzständer-Konstruktionen oder zwischen Holzbalken.</p>

IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.