



CUT LENGTHWISE



CUT CROSSWISE

VIEW

ROC Typ 3

swissporROC
swisspor AG

<http://www.swisspor.ch/> | info@swisspor.com

Type: **Insulation | Cemented**

swissporROC - Steinwolle ist ein vielseitiger Dämmstoff auf anorganischer Basis. Je nach Rohdichte und Ausführung eignet sich swissporROC für Anwendungen rund um die Gebäudehülle, mit Ausnahme im Perimeterbereich. Bemerkenswert ist der hohe Schmelzpunkt von über 1000 °C.

mtextur ID	88544
Manufacturer	swisspor AG
Manufacturer-Email	info@swisspor.com
Product Line	swissporROC
Product Line Info	swissporROC - Steinwolle ist ein vielseitiger Dämmstoff auf anorganischer Basis. Je nach Rohdichte und Ausführung eignet sich swissporROC für Anwendungen rund um die Gebäudehülle, mit Ausnahme im Perimeterbereich. Bemerkenswert ist der hohe Schmelzpunkt von über 1000 °C.
Material Name	ROC Typ 3
Type	Insulation / Cemented
eBKP	C 1.2 Abdichtung, Dämmung und Bodenplatte / C 1.2 Waterproofing/insulation below ground slab / C 2.1 Aussenwandkonstruktion / C 2.1 External walls / C 4.4 Dachkonstruktion / C 4.4 Roof structure, roof slabs
IFC	IfcCovering / IfcSlab / IfcSlab.Floor / IfcWall
Area of application (mtextur Classic)	Inside / Floor / Wall / Ceiling / Roof / Facade Outside / Floor / Wall / Ceiling / Roof / Facade
Delivery zones	CH / LI
Size of the CAD & BIM texture	Height: 200.0 mm / Width: 200.0 mm

IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.

max. Length / Format	Length = 1250 mm / Width = 600 mm / Thickness = 160 mm
min. Format	Length = 1250 mm / Width = 600 mm / Thickness = 30 mm
Weight	52.0 kg/m ³
Thermal Conductivity	0.031 W/mK
Fire protection class	6q.3 A1
Characteristics Info	Steife Dämmplatten, durchgehend imprägniert. Wärme- und Schalldämmung für hinterlüftete Fassaden oder Rauntrennwände. Beim Dach für Sparrendach auf der Schalung, Beton- oder Hallensteildach auf Profilblech.

IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.